

FlashRunner Series Comparison Table



DC10079

Features	FlashRunner I Series					FlashRunner II Series	FlashRunner III Series
	FR01ENG	FR01LAN	FR01ATO	FR01M01	FR01PRO		
Programming Support	Universal	Universal	Universal	Universal	Universal	One Manuf.	One Manuf.
Host Interface(s)	RS-232	LAN, RS-232	LAN, RS-232	LAN, RS-232	LAN, RS-232	LAN, RS-232	RS-232
ISP Sites	1	1	1 (Switchable to ATE)	8 (Multiplexed)	1	1	1
ISP Connector Type	Header	D-Sub	DIN 41612	Header	D-Sub	D-Sub	D-Sub
Power Supply	9-24V DC	9-24V DC	9-24V DC	9-24V DC	110/220V AC	9-24V DC	7.5V DC
SD Card (FAT16, up to 2GB)	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Logs/Reports	Yes	Yes	Yes	Yes	Yes	Yes	No
On-Board Dynamic Memory	512 Bytes	512 Bytes	512 Bytes	512 Bytes	512 Bytes	512 Bytes	-
IP Piracy Protection	Yes	Yes	Yes	Yes	Yes	Yes	No
Scripts (Host Mode)	Unlimited	Unlimited	Unlimited	Unlimited	Unlimited	Unlimited	Unlimited
Scripts (Standalone Mode)	32	32	32	32	32	32	1
Dimensions (mm)	130 x 74 x 27	130 x 74 x 43	130 x 74 x 43	130 x 74 x 43	360 x 210 x 45	130 x 74 x 43	90 x 65 x 35
Real-Time Clock/Calendar	Yes	Yes	Yes	Yes	Yes	Yes	No
Optoisolation	Yes	Yes	Yes	Yes	Yes	Yes	No