

SPRAY PARTS WASHER

X800



SHEET 01/23

Some characteristics may be subject to changes that do not affect the purpose of use of the product.

GENERAL FEATURES

Washing machines with rotating platform for spray washing industrial products with heated solutions with water and detergent. Made of stainless steel and with quality components for industrial use. Designed and manufactured entirely in Italy and CE certified.

They are equipped with: round basket moved by a gear motor; spraying ramps placed underneath, to the side and above the products to be treated; movable upper ramp to facilitate loading/unloading; hinged top cover, with safety micro, gas pistons and sealing gasket; float for stopping the pump and heating elements; electric heating element liquids.

The electromechanical control panel allows you to adjust the temperature and washing time.

Models equipped with drying and disc oil separator are available.

SPECIFICATIONS

Tank capacity	140 lt
Maximum system dimensions (H x W x D)	1394 x 1119 x 1013 mm
Basket size (diameter x H)	800 x 500 mm
Total system weight	150 kg
Reach	150 kg
Useful washing height	500 mm
Gear motor power / rotation speed:	0.12 kW / 5 Rpm
Hourly production capacity	6-10 cycles/h
Washing tank capacity	140 lt
Washing tank heating power	6 kW
Tank working temperature	60°/70°
Washing pump power	0.9 kW
Power supply	400V 3ph/50Hz
Total installed power	9.32 kW
Vacuum power (if present)	0.09 kW
Removable residue filter	Present

AVAILABLE OPTIONS

Rinse tank | Dewatering with blower | Dewatering with heater | aspiratore Base with drip tray | External mobile trolley + drip tray | Reinforced Basket | Reinforced Basket with 120° Supports | Standard Basket | Disc Oil Separator | small bag filter | bag filter size 2 | thermal insulation | Manual Wash with Sprayer | Pulse Blowing | oversized pump | Logo Programmer 8 | valvole di sucmento Base with self-braking wheels

COMMERCIAL PHOTOS

